



TT-328 Multi Super 5

WATER REPELLANT, LUBRICANT, PROTECTOR, CLEANER AND LOOSENER

- ✓ Repels water and moisture (extremely low surface tension).
- ✓ Provides a light but effective and precision lubrication for machinery.
- ✓ Provides longterm protection against corrosion.
- ✓ Cleans both machines and polished surfaces; keeps rubbers soft and flexible.
- ✓ Strong and fast penetration. Loosens rust and corrosion in hard to reach areas.

Technical Info

- Specific weight: 0,811 at 20°C.
- Flashpoint: 52°C.
- Boiling point: 116°C.
- Solidity point: none until -62°C.
- Viscosity at 38°C: 2 mPa.s.
- Dielectrical constant: 33 KV min/215 mm (ASTMD-877).
- Lubrication capacity: more than 226 kg (Falex step test).
- Shelf life: 48 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

Packing

TT-328 Multi Super 5 - can 5L	232002118
TT-328 Multi Super 5 - can 25L	232020118
TT-328 Multi Super 5 - aerosol 400ml	232001118
TT-328 Multi Super 5 - barrel 200L	232000118

Product

Characteristics

- Provides a high capillary effect and good creeping action. It penetrates into the smallest cavities causing a chemical attack which loosens the rust.
- Contains no silicones or graphite.

Applications

- to release jammed screws, bolts and nuts, pipe fittings and joints
- to repel moisture form ignition contacts and electrical leads, and protects them
- to lubricate and clean brake linkages, cables and all kinds of chains
- to protect metal surfaces from corrosion

Use

- Shake before use.
 - Apply.
 - Let it work.
- Allow propellants to evaporate if necessary.