



TT-917 Stop Oil HD

SEALS OIL LEAKS FROM HEAVY EQUIPMENT

- ✓ Stops and prevents drying and hardening of all plastic seals and gaskets.
- ✓ Makes rubbers soft in one treatment.
- ✓ Compatible with all Heavy Duty oil types, including thick differential oil.
- ✓ Free from chlorides, solvents and oil thickeners.

Technical Info

- Composition: liquid oily mixture of selected rubber softeners.
- Odour: slight oily smell.
- Density: ca 1.15 +/- 0.1 kg/dm³.
- Solubility: mixable with all oils; soluble in solvents and insoluble in water.
- Flashpoint: 235°C.
- Consumption: 30 ml/l oil.
- Shelf life: 24 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

Packing

TT-917 Stop Oil HD - can 5L

742153118

Product

Characteristics

Stop Oil HD prevents expensive disassembly and assembly costs for replacement of leaking seals. Stop Oil HD conditions seals, protects them against dehydration, hardening, shrinking and crystallisation. Stop Oil HD impregnates the leaking seals, makes them elastic again, lets them swell in a controlled way and rules out oil leakages for a long time. Stop Oil HD as a curative treatment does not need to be repeated. Once its work is done, the condition of the seals is as new. Also suitable for ATF, hydraulic and mineral oils. Stop Oil HD as a preventive treatment is recommended for engines and installations as from 3 years old.

Applications

- Combatting oil leaks in closed oils systems
- Effective on all rubber seals and most cork seals in diesel and petrol engines, hydraulic systems, hydro-pneumatic spring systems, gearboxes,...

Use

- Add 30 ml per liter of fresh oil.
- Do this after oil change to make Stop Oil HD work better and longer.
- Use the vehicle or application regularly to heat up the oil and circulate to promote the effect of Stop Oil HD.