



# TT-708 Nova PTFE Care

DURABLE PTFE-TREATMENT FOR ENGINE, GEARBOX AND DIFFERENTIAL

- ✓ Prevents friction and protects all moving parts.
- ✓ Prevents sludge and protects against acids.
- ✓ Increases performance, reduces exhaust emissions and extends service life.
- ✓ Fast action with sustainable effect.

## Technical Info

- Boiling point: 48 °C.
- Flashpoint: 215°C.
- Melting point: 300 °C.
- pH:4-8.
- Relative density (at 20°C): 0,89.
- Relative vapour density: > 1.
- Water solubility: insoluble.
- Odour: ether-like.
- Colour: colourless.
- Shelf life: 36 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

## Packing

TT-708 Nova PTFE Care - bottle 300ml

741403118

## Product

### Characteristics

Nova PTFE Care is a concentrated friction reducer through durable PTFE treatment for engine, gearbox and differential. 1 treatment is good for 80,000 km. Nova PTFE Care reduces oil consumption and extends the life of all moving parts by applying a PTFE film that prevents metal friction.

### Applications

Suitable for diesel and gasoline engines.  
Can be used in all manual gearboxes.

## Use

- For optimal result: clean first.
  - Bring the engine at operating temperature.
  - Add half of the bottle in the engine to the clean engine oil.
  - Shake the bottle powerfully and add the rest.
- Nova PTFE Care treats up to 5 litres of oil.