



# TT-185 Kabelfedt

LUBRICANT FOR ASSEMBLY AND DISASSEMBLY

- ✓ Effective on all plastic parts, with or without rubber seals.
- ✓ Simplifies the "pass through" of electrical wiring.
- ✓ Safe, quick-drying and almost without residue.

## Technical Info

- Base: soap emulsion.
- Form: liquid.
- Colour: transparent-white.
- Melting point: 0°C.
- Boiling point: 100°C - 221°C.
- pH value: 8.
- Flashpoint: 70°C.
- Self-ignition: 255°C.
- Shelf life: 36 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

## Packing

TT-185 Kabelfedt - aerosol 400ml

233985118

## Product

### Characteristics

- A spray for the assembly and disassembly of any synthetic materials and makes it easier to push/pull cables through pipes.
- A lubricant for all types of cables.

### Applications

- In the electricity industry, as well as sanitary installations, HVAC, domotics, ...
- Makes it easier to push/pull cabling through pipes.
- With coaxial cables, TT-185 Kabelfedt prevents the central core to break under severe strain.
- The pre-flexible cable is easier to pull through cable ducts.
- Makes it easier to install rubbers in verandas & greenhouses, easy to remove on glass.
- Makes it easier to assemble solar collectors.

## Use

- Shake before use.
- Spray on the application.
- Act immediately.